

156-00468



Article Number: 156-00468

Cable Tie and Edge Clip, 50lb, 8.0" Long, EC5, Panel Thickness .04"-.12", PA66UV, Black, 100/bag



## Base Data

Local Order Number 156-00468

Type T50REC5B

Color Black (BK)

- Features and Benefits**
- Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.
  - Edge Clip provides low insertion force and high extraction force ideal for assembly environments.
  - Two piece assembly allows the mount to slide along the strap ensuring proper orientation.
  - Cable tie is outside serrated to reduce bundle chafing.

**Product Description** The cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.

**Fixation Method (FF)** EdgeClip, sideways, assembled, 2 piece

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Variant** Inside Serrated

**Short Description** Cable Tie and Edge Clip, 50lb, 8.0" Long, EC5, Panel Thickness .04"-.12", PA66UV, Black, 100/bag

## Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225 N

Length L (imperial) 8.0 "

Length L (metric) 200.0 mm

Length L2 (imperial) 0.6 "

Length L2 (metric) 14.0 mm

Width W (imperial) 0.18 "

Width W (metric) 4.6 mm

Width W2 (imperial) 0.4 "

Width W2 (metric) 10.0 mm

Height H (imperial) 0.05 "

Height H (metric) 1.2 mm

Height H2 (imperial) 0.4 "

Height H2 (metric) 10.8 mm

Bundle Diameter min (imperial) 0.2 "

Bundle Diameter min (metric) 4.0 mm

Bundle Diameter max (imperial) 2.0 "

Bundle Diameter max (metric) 50.0 mm

<b>Panel Thickness max. (imperial)</b>	0.12 "
<b>Panel Thickness max. (metric)</b>	3.0 mm
<b>Panel Thickness min. (imperial)</b>	0.04 "
<b>Panel Thickness min. (metric)</b>	1.0 mm
<b>Thickness T (imperial)</b>	0.05 "
<b>Thickness T (Metric)</b>	1.2 mm

## Logistics and Packaging

---

<b>Quantity per</b>	bag
<b>Package Quantity</b>	100
<b>Carton Quantity</b>	2500

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyamide 6.6 UV-stabilized (PA66UV)
<b>Material Shortcut</b>	PA66HIRHSUV PA66UV
<b>Material Cable Tie</b>	Polyamide 6.6 UV-stabilized (PA66UV)
<b>Material Edge Clip</b>	Stainless Steel (SS) Polyamide 6 high impact modified, heat stabilised (PA6HIRHS)
<b>Flammability</b>	UL94 V2 UL94 HB
<b>Operating Temperature</b>	-40 °F to +230 °F (-40 °C to +110 °C) -40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes