

169-60020



Article Number: 169-60020

Convoluted Tubing, Slit, 0.75" Diameter, PA6, Black, 100ft/pkg



## Base Data

Local Order Number 169-60020

Type CTN340

Color Black (BK)

- Features and Benefits**
- Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture
  - Tubing protects cables and wires against automotive fluids, vibration wear
  - Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight

**Product Description** HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.

**Short Description** Convoluted Tubing, Slit, 0.75" Diameter, PA6, Black, 100ft/pkg

## Product Dimensions

Length L (imperial) 100.0 ft

Length L (metric) 30.48 m

Diameter D (imperial) 0.989 "

Diameter D (metric) 25.12 mm

Diameter D2 (imperial) 0.759 "

Diameter D2 (metric) 19.28 mm

Nominal Diameter (imperial) 0.75 "

Nominal Diameter (metric) 19.05 mm

Wall Thickness WT (imperial) 0.005 "

Wall Thickness WT (metric) 0.127 mm

## Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 100.0 ft

Package Quantity 30.48 m

## Material and Specifications

Material Polyamide 6 (PA6)

Material Shortcut PA6

Operating Temperature -40 °F to +300 °F (-40 °C to +149 °C)

ROHS Conformity Yes

