

170-03011



Article Number: 170-03011

Flame Retardant Expandable Braided Sleeving, 1.5" Dia., Black, 40.0 ft/Standard Reel



## Base Data

Local Order Number 170-03011

Type BSPFR1120

Color Black (BK)

**Features and Benefits**

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

**Product Description** A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Open Post Termination No

Short Description Flame Retardant Expandable Braided Sleeving, 1.5" Dia., Black, 40.0 ft/Standard Reel

## Product Dimensions

Length L (imperial) 40.0 ft

Length L (metric) 12.2 m

Bundle Diameter min (imperial) 1.0 "

Bundle Diameter min (metric) 25.4 mm

Bundle Diameter max (imperial) 2.125 "

Bundle Diameter max (metric) 53.9 mm

Nominal Diameter (imperial) 1.5 "

Nominal Diameter (metric) 38.1 mm

## Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 40 ft

Package Quantity 40.0 ft

Reel Length (imperial) 40.0 ft

Reel Length (metric) 12.2 m

Weight (imperial) 0.79 lbs

Weight (Metric) 0.358 kg

## Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability FAR 25

VW-1  
Mil-202  
FMVSS 302

**Melting Point** +250 °C

**Operating Temperature** -94 °F to +257 °F (-70 °C to +125 °C)

**ROHS Conformity** Yes

**UL Recognized (US and Canada)** Yes