

170-03020



Article Number: 170-03020

Fray Resistant Flame Retardant Expandable Braided Sleeveing, 1.25" Dia., Black, 50.0 ft/Standard Reel



## Base Data

Local Order Number 170-03020

Type BSSCFR1140

Color Black (BK)

- Features and Benefits**
- Increased braid density coverage provides higher level of abrasion resistance without losing flexibility.
  - Treated yarns extinguish quickly and reduces potential flame spread to surrounding components.
  - Cuts with ordinary scissors without fraying ends.

**Product Description** Treated polyester yarns that can be cut with sharp scissors and provides flame retardant properties. Well suited for situations where access to a hot knife is either impractical or impossible. Contains white tracer thread for easy identification.

Open Post Termination No

**Short Description** Fray Resistant Flame Retardant Expandable Braided Sleeveing, 1.25" Dia., Black, 50.0 ft/Standard Reel

## Product Dimensions

Length L (imperial) 50.0 ft

Length L (metric) 15.2 m

Bundle Diameter min (imperial) 1.0 "

Bundle Diameter min (metric) 25.4 mm

Bundle Diameter max (imperial) 1.5 "

Bundle Diameter max (metric) 38.1 mm

Nominal Diameter (imperial) 1.25 "

Nominal Diameter (metric) 31.8 mm

## Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 50 ft

Reel Length (imperial) 50.0 ft

Reel Length (metric) 15.2 m

Weight (imperial) 0.78 lbs

Weight (Metric) 0.35 kg

## Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability UL VW-1  
Mil-202

Melting Point +250 °C

**Operating Temperature** -94 °F to +257 °F (-70 °C to +125 °C)

**ROHS Conformity** Yes

**UL Recognized (US and Canada)** Yes