

## CTN380STD



Article Number: 169-60015

Convoluted Tubing, Slit, 0.375" Diameter, PA6, Black w/Gray Stripe, 1900ft/pkg



Download drawing

### Base Data

<b>Local Order Number</b>	CTN380STD
<b>Type</b>	CTN380
<b>Color</b>	Black with Gray Stripe (BKSTGY)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture</li> <li>• Tubing protects cables and wires against automotive fluids, vibration wear</li> <li>• Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight</li> </ul>
<b>Product Description</b>	HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
<b>Short Description</b>	Convoluted Tubing, Slit, 0.375" Diameter, PA6, Black w/Gray Stripe, 1900ft/pkg

### Product Dimensions

<b>Length L (imperial)</b>	1900.0 ft
<b>Length L (metric)</b>	579.12 m
<b>Diameter D (imperial)</b>	0.526 "
<b>Diameter D (metric)</b>	13.36 mm
<b>Diameter D2 (imperial)</b>	0.38 "
<b>Diameter D2 (metric)</b>	9.652 mm
<b>Nominal Diameter (imperial)</b>	3/8 "
<b>Nominal Diameter (metric)</b>	9.652 mm
<b>Wall Thickness WT (imperial)</b>	0.005 "
<b>Wall Thickness WT (metric)</b>	0.127 mm

### Logistics and Packaging

<b>Quantity per</b>	carton
<b>Package Quantity (imperial)</b>	1900.0
<b>Package Quantity</b>	579.1 m
<b>Carton Quantity</b>	1900

### Material and Specifications

<b>Material</b>	Polyamide 6 (PA6)
<b>Material Shortcut</b>	PA6
<b>Operating Temperature</b>	-40°F to +300°F (-40°C to +149°C)

ROHS Conformity Yes

---

© HellemannTyton 2014