

111-00468



Article Number: 111-00468

Standard Cable Tie, 8" Long, 50lb Tensile Strength, PA66UV, Red, 100/pkg



Base Data

Local Order Number 111-00468

Type T50R

Color Red (RD)

- Features and Benefits**
- UV stabilized cable ties contain an inhibitor which prolongs the life of the tie in UV exposures .
 - Inside serrations allow for strong hold on cables and wire bundles.
 - Head design provides high tensile strength with very low insertion force.
 - Bent tail ensures a quick and simple installation.

Product Description HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Standard Cable Tie, 8" Long, 50lb Tensile Strength, PA66UV, Red, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225.0 N

Length L (imperial) 8.0 "

Length L (metric) 202.0 mm

Width W (imperial) 0.18 "

Width W (metric) 4.6 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.5 mm

Bundle Diameter max (imperial) 1.97 "

Bundle Diameter max (metric) 50.0 mm

Logistics and Packaging

Package Quantity 100

Material and Specifications

Material Polyamide 6.6 UV-resistant (PA66UV)

Material Shortcut PA66UV

Flammability UL94 V2

Halogenfree Yes

Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)

ROHS Conformity Yes

Certification / Specification MIL 53421
UL ZODZ2.E64139

UL Listed (US and Canada) No

UL Recognized (US and Canada) No