

111-00718



Article Number: 111-00718

High Temp Cable Tie, 15" Long, 50lb Tensile Strength, ETFE, Blue, 100/pkg

 RoHS

Base Data

Local Order Number	111-00718
Type	T50L
Color	Blue (BU)
Features and Benefits	• ETFE cable ties provide excellent resistance to chemicals, radiation, high temperatures and UV exposure. • Inside serrations allows for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Product Description	HellermannTyton high temperature cable ties are made of specially formulated materials providing various levels of temperature resistance and performance. The cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Fixation Method (FF)	None
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	High Temp Cable Tie, 15" Long, 50lb Tensile Strength, ETFE, Blue, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	50.0 lbs
Minimum Tensile Strength (N)	222.3 N
Length L (imperial)	15.0 "
Length L (metric)	382.0 mm
Width W (imperial)	0.19 "
Width W (metric)	4.7 mm
Bundle Diameter min (imperial)	0.2 "
Bundle Diameter min (metric)	5.0 mm
Bundle Diameter max (imperial)	4.1 "
Bundle Diameter max (metric)	105 mm
Thickness T (imperial)	0.06 "
Cable Tie Head Height (Metric)	5.9 mm
Cable Tie Head Length (metric)	8.6 mm
Cable Tie Head Width (metric)	8.7 mm
Cable Tie Head Length (imperial)	0.34 "
Cable Tie Head Width (imperial)	0.33 "

Thickness T (Metric) 1.7 mm

Logistics and Packaging

Quantity per bag
Package Quantity 100
Carton Quantity 5000
Weight (Metric) 2.7 kg

Material and Specifications

Material Ethylentetrafluorineethylene - (E/TFE)
Material Shortcut E/TFE
Flammability UL94 V0
Operating Temperature -112 °F to +338 °F (-80 °C to +170 °C)
ROHS Conformity Yes
UL Listed (US and Canada) No
UL Recognized (US and Canada) Yes