

111-00815

Article Number: 111-00815

High Temp Tie, 8" Long, 50lb Tensile Strength, PA46, Natural, 100/pkg

HellermannTyton



## Base Data

Local Order Number 111-00815

Type T50R

Color Natural (NA)

- Features and Benefits**
- Cable ties made of PA46 material provide a greater resistance to high heat exposures than PA66 heat stabilized material.
  - Inside serrations allow for strong hold on cables and wire bundles.
  - Head design provides high tensile strength with very low insertion force.
  - Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton high temperature cable ties are made of specially formulated materials providing various levels of temperature resistance and performance. The cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description High Temp Tie, 8" Long, 50lb Tensile Strength, PA46, Natural, 100/pkg

## Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225.0 N

Length L (imperial) 8.0 "

Length L (metric) 202.0 mm

Width W (imperial) 0.18 "

Width W (metric) 4.6 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.5 mm

Bundle Diameter max (imperial) 1.97 "

Bundle Diameter max (metric) 50.0 mm

## Logistics and Packaging

Quantity per bag

Package Quantity 100

Carton Quantity 5000

## Material and Specifications

---

<b>Material</b>	Polyamide 4.6 (PA46)
<b>Material Shortcut</b>	PA46
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +275 °F (-40 °C to +135 °C)
<b>ROHS Conformity</b>	Yes
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	No