

111-01125



**Article Number: 111-01125**

**High Temp Cable Tie, 15.2" Long, 120lb Tensile Strength, ETFE, Blue, 50/pkg**



## Base Data

**Local Order Number** 111-01125

**Type** T120R

**Color** Blue (BU)

- Features and Benefits**
- ETFE cable ties provide excellent resistance to chemicals, radiation, high temperatures and UV exposure.
  - Inside serrations allows for strong hold on cables and wire bundles.
  - Head design provides high tensile strength with very low insertion force.
  - Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton high temperature cable ties are made of specially formulated materials providing various levels of temperature resistance and performance. The cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** High Temp Cable Tie, 15.2" Long, 120lb Tensile Strength, ETFE, Blue, 50/pkg

## Product Dimensions

**Minimum Tensile Strength (imperial)** 120.0 lbs

**Minimum Tensile Strength (N)** 535.0 N

**Length L (imperial)** 15.2 "

**Length L (metric)** 387.0 mm

**Width W (imperial)** 0.29 "

**Width W (metric)** 7.4 mm

**Bundle Diameter min (imperial)** 0.59 "

**Bundle Diameter min (metric)** 15.0 mm

**Bundle Diameter max (imperial)** 4.1 "

**Bundle Diameter max (metric)** 105.0 mm

**Thickness T (imperial)** 0.075 "

**Cable Tie Head Height (Metric)** 8.7 mm

**Cable Tie Head Length (metric)** 12 mm

**Cable Tie Head Width (metric)** 12.95 mm

**Cable Tie Head Length (imperial)** 0.47 "

**Cable Tie Head Width (imperial)** 0.51 "

Thickness T (Metric) 1.9 mm

## Logistics and Packaging

---

**Package Quantity** 50  
**Carton Quantity** 2000 Pieces  
**Weight (Metric)** 5.2 kg

## Material and Specifications

---

**Material** Ethylentetrafluorethylene - (E/TFE)  
**Material Shortcut** E/TFE  
**Flammability** UL94 V0  
**Operating Temperature** -112 °F to +338 °F (-80 °C to +170 °C)  
**ROHS Conformity** Yes  
**UL Listed (US and Canada)** No  
**UL Recognized (US and Canada)** Yes