

111-01126

Article Number: 111-01126

Heavy Duty Cable Tie, 40.6" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

HellermannTyton



Base Data

Local Order Number 111-01126

Type T250XL

Color Black (BK)

Features and Benefits

- High impact, heat and UV stabilized heavy duty cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.
- Heavy duty design to offer higher tensile strength.
- Buckle feature on head allows excess strap to be tucked away after installation.

Product Description HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Variant Inside Serrated

Short Description Heavy Duty Cable Tie, 40.6" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 250.0 lbs

Minimum Tensile Strength (N) 1115.0 N

Length L (imperial) 40.6 "

Length L (metric) 1030.0 mm

Width W (imperial) 0.49 "

Width W (metric) 12.5 mm

Bundle Diameter min (imperial) 0.47 "

Bundle Diameter min (metric) 12.0 mm

Bundle Diameter max (imperial) 12.0 "

Bundle Diameter max (metric) 305.0 mm

Logistics and Packaging

Quantity per bag

Package Quantity 25

Carton Quantity 250

Material and Specifications

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL94 HB

Halogenfree No

Operating Temperature -40 °F to +230 °F (-40 °C to +110 °C)

ROHS Conformity Yes

UL Listed (US and Canada) No

UL Recognized (US and Canada) No