

111-01138



Article Number: 111-01138

Heavy Duty Cable Tie, 8.9" Long, 120lb Tensile Strength, PA66HIRHSUV, Black, 500/pkg



Base Data

Local Order Number 111-01138

Type T120S

Color Black (BK)

Features and Benefits

- High impact, heat and UV stabilized heavy duty cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.
- Head design provides high tensile strength with very low insertion force.
- Bent tail ensures a quick and simple installation.

Product Description HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Heavy Duty Cable Tie, 8.9" Long, 120lb Tensile Strength, PA66HIRHSUV, Black, 500/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 120.0 lbs

Minimum Tensile Strength (N) 535.0 N

Length L (imperial) 8.9 "

Length L (metric) 225.0 mm

Width W (imperial) 0.3 "

Width W (metric) 7.6 mm

Bundle Diameter min (imperial) 0.2 "

Bundle Diameter min (metric) 5.0 mm

Bundle Diameter max (imperial) 2.2 "

Bundle Diameter max (metric) 55.0 mm

Logistics and Packaging

Package Quantity 500

Carton Quantity 1000

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHSUV

Flammability UL94 HB

Halogenfree Yes

Operating Temperature -40 °F to +230 °F (-40 °C to +110 °C)

ROHS Conformity Yes

UL Listed (US and Canada) No

UL Recognized (US and Canada) No