

111-01302

Article Number: 111-01302

Stainless Steel Tie, 20.5" Long, 922lb Tensile Strength, SS316, Metal, 50/pkg



Base Data

Local Order Number 111-01302

Type MBT20UH

Color Metal (ML)

Features and Benefits

- 316 grade stainless steel offers excellent resistance to salt spray, corrosion, weather and chemical resistance.
- Ball bearing locking mechanism assures high tensile strength and easy insertion.

Product Description HellermannTyton's stainless steel ties are designed with a ball bearing locking mechanism to assure high tensile strength and easy insertion when securing hoses, cables, pipes and more. Available in 304 or 316 grades of stainless steel, providing protection when used in corrosive environments, fire resistance and temperature extremes.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure ball bearing lock

Variant No Serration

Short Description Stainless Steel Tie, 20.5" Long, 922lb Tensile Strength, SS316, Metal, 50/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 922.0 lbs

Minimum Tensile Strength (N) 4100.0 N

Length L (imperial) 20.5 "

Length L (metric) 521.0 mm

Width W (imperial) 0.63 "

Width W (metric) 16.0 mm

Bundle Diameter min (imperial) 0.47 "

Bundle Diameter min (metric) 12.0 mm

Bundle Diameter max (imperial) 6.0 "

Bundle Diameter max (metric) 152.0 mm

Logistics and Packaging

Quantity per bag

Package Quantity 50

Carton Quantity 500

Material and Specifications

Material Stainless Steel (SS316)

Material Shortcut SS316

Flammability non-burning

Halogenfree Yes

Operating Temperature -112 °F to +1000 °F (-80 °C to +538 °C)

ROHS Conformity Yes