

111-05350



Article Number: 111-05350

FirTreeMount/Cable Tie 30lb 11.8" Mnt Hole Dia .256"-.276"Pan Thk .031"-.276" PA66HIRHS,Black,500/pk



## Base Data

Local Order Number 111-05350

Type T50IFT7

Color Black (BK)

**Features and Benefits** HellermannTyton's fir tree mounts provide a secure grip in a mounting hole and protect against dirt and other impurities. The mount can slide along the strap of the cable tie for proper orientation. The fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.

Fixation Method (FF) Fir Tree

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description FirTreeMount/Cable Tie 30lb 11.8" Mnt Hole Dia .256"-.276"Pan Thk .031"-.276" PA66HIRHS,Black,500/pk

## Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225 N

Length L (imperial) 11.8 "

Length L (metric) 300 mm

Length L2 (imperial) 0.46 "

Length L2 (metric) 11.6 mm

Length L3 (imperial) 0.75 "

Length L3 (metric) 19 mm

Width W (imperial) 0.18 "

Width W (metric) 4.6 mm

Width W2 (imperial) 0.457 "

Width W2 (metric) 11.6 mm

Width W3 (imperial) 0.2 "

Width W3 (metric) 5.0 mm

Height H (imperial) 0.0472 "

Height H (metric) 1.2 mm

Height H2 (imperial) 0.5 "

Height H2 (metric) 12.7 mm

Bundle Diameter min (imperial) 0.158 "

Bundle Diameter min (metric) 5.0 mm

<b>Bundle Diameter max (imperial)</b>	3.35 "
<b>Bundle Diameter max (metric)</b>	85.0 mm
<b>Disc Diameter (imperial)</b>	0.63 "
<b>Disc Diameter (metric)</b>	16.0 mm
<b>Panel Thickness max. (imperial)</b>	0.276 "
<b>Panel Thickness max. (metric)</b>	7.00 mm
<b>Panel Thickness min. (imperial)</b>	0.031 "
<b>Panel Thickness min. (metric)</b>	0.80 mm
<b>Mounting Hole Diameter D (metric)</b>	6.5 - 7.0 mm
<b>Mounting Hole Diameter D min (imperial)</b>	0.256 "
<b>Mounting Hole Diameter D max (imperial)</b>	0.276 "

---

## Logistics and Packaging

<b>Quantity per</b>	bag
<b>Package Quantity</b>	500
<b>Carton Quantity</b>	2000 Pieces
<b>Weight (Metric)</b>	2 kg

---

## Material and Specifications

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Material Cable Tie</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Edge Clip</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +221 °F (-40 °C to +105 °C)
<b>ROHS Conformity</b>	Yes