

115-00030

Article Number: 115-00030

Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Black, 5/pkg



## Base Data

Local Order Number 115-00030

Type RTT750HR

Color Black (BK)

**Features and Benefits**

- The heavy duty Speedy tie features a specially designed head and patented trigger to allow for repeated use in temporary bundling applications.
- Additional design feature on the head allows excess strap to be tucked away after installation.

**Product Description** HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes or temporary bundling are necessary. The head design guarantees high tensile strength even after repeated use.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) Yes

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Black, 5/pkg

## Product Dimensions

Minimum Tensile Strength (imperial) 200.0 lbs

Minimum Tensile Strength (N) 888.0 N

Length L (imperial) 29.6 "

Length L (metric) 752.0 mm

Width W (imperial) 0.51 "

Width W (metric) 13.0 mm

Bundle Diameter min (imperial) 1.6 "

Bundle Diameter min (metric) 40.0 mm

Bundle Diameter max (imperial) 8.3 "

Bundle Diameter max (metric) 210 mm

Thickness T (imperial) 0.075 "

Thickness T (Metric) 1.9 mm

## Logistics and Packaging

Quantity per pc

Package Quantity 5

Carton Quantity 60 Pieces

Weight (Metric) 23.2 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 high impact modified, scan black (PA66HIR(S))
<b>Material Shortcut</b>	PA66HIR(S)
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40 °F to +176 °F (-40 °C to +80 °C)
<b>ROHS Conformity</b>	Yes