

115-06960

Article Number: 115-06960

Arrowhead Push Tie, 9.0" Length, 2.0" Bundle Diameter, PA66, Black, 1,000/pkg

HellermannTyton



Base Data

Local Order Number 115-06960

Type RT50SFK

Color Black (BK)

- Features and Benefits**
- Arrowhead is easy to install without the need for use with a tool.
 - Arrowhead gives a firm and secure fixing and can be used in multiple panel thicknesses.
 - Design provides low insertion and high extraction force ideal for the production environment.

Product Description Arrowhead Ties ensure a firm and secure fixing. The legs take up any variation in panel thickness enabling one part to suit many applications. These are quick and easy to install, and can be used with various surfaces such as sheet metal, wood, and cast iron.

Fixation Method (FF) Arrowhead

Identification Plate Position none

Releasable Closure (Yes/No) Yes

Short Description Arrowhead Push Tie, 9.0" Length, 2.0" Bundle Diameter, PA66, Black, 1,000/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225 N

Length L (imperial) 9.0 "

Length L (metric) 225 mm

Width W (imperial) 0.2 "

Width W (metric) 5.0 mm

Width W2 (imperial) 0.6 "

Width W2 (metric) 14.7 mm

Height H (imperial) 0.24 "

Height H (metric) 6 mm

Bundle Diameter min (imperial) 0.24 "

Bundle Diameter min (metric) 6.0 mm

Bundle Diameter max (imperial) 2.0 "

Bundle Diameter max (metric) 50.0 mm

Panel Thickness max. (imperial) 0.03 "

Panel Thickness max. (metric) 3.0 mm

Panel Thickness min. (imperial) 0.31 "

Panel Thickness min. (metric) 0.8 mm

Mounting Hole Diameter D (imperial) 0.25 - 0.28 "

Mounting Hole Diameter D (metric) 6.4 - 7.0 mm

**Mounting Hole Diameter D min
(imperial)** 0.26 "

**Mounting Hole Diameter D max
(imperial)** 0.275 "

Thickness T (imperial) 0.055 "

**Mounting Hole Diameter D max
(metric)** 7.0 mm

Mounting Hole Diameter D min (metric) 6.4 mm

Thickness T (Metric) 1.4 mm

Logistics and Packaging

Quantity per bag

Package Quantity 1000

Carton Quantity 6000 Pieces

Weight (Metric) 1.93 kg

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)

ROHS Conformity Yes