

118-05050

**Article Number:** 118-05050

**Outside Serrated Cable Ties, 50lb. 8" Max. Bun. Dia 1.95" PA66HS, Black, 100/pk**



## Base Data

**Local Order Number** 118-05050

**Type** T50ROS

**Color** Black (BK)

**Features and Benefits** The OS range of outside serrated cable ties offers high tensile strengths, low insertion force and a smooth surface to the cable - minimizing any indentation or damage to the insulation. The curved shape of the head allows the tie to follow the contours of the cable and takes up less space than other tie designs.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Outside Serrated

**Short Description** Outside Serrated Cable Ties, 50lb. 8" Max. Bun. Dia 1.95" PA66HS, Black, 100/pk

## Product Dimensions

**Minimum Tensile Strength (imperial)** 50.0 lbs

**Minimum Tensile Strength (N)** 225 N

**Length L (imperial)** 8.0 "

**Length L (metric)** 200 mm

**Width W (imperial)** 0.18 "

**Width W (metric)** 4.6 mm

**Height H (imperial)** 0.051 "

**Height H (metric)** 1.3 mm

**Bundle Diameter min (imperial)** 0.063 "

**Bundle Diameter min (metric)** 1.6 mm

**Bundle Diameter max (imperial)** 1.95 "

**Bundle Diameter max (metric)** 50.0 mm

**Thickness T (imperial)** 0.05 "

**Cable Tie Head Height (Metric)** 5.9 mm

**Cable Tie Head Length (metric)** 6.75 mm

**Cable Tie Head Width (metric)** 7.9 mm

**Cable Tie Head Length (imperial)** 0.26 "

**Cable Tie Head Width (imperial)** 0.31 "

**Thickness T (Metric)** 1.3 mm

## Logistics and Packaging

---

<b>Quantity per</b>	bag
<b>Package Quantity</b>	100
<b>Carton Quantity</b>	7000 Pieces
<b>Weight (Metric)</b>	1.3 kg

---

## Material and Specifications

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL94 V2
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-40 °F to +221 °F (-40 °C to +105 °C)
<b>ROHS Conformity</b>	Yes