

118-05850

Article Number: 118-05850

Outside Serrated Cable Ties, 50lb. 5.9" Max. Bun. Dia 1.38" PA66HS, Black, 100/pk



Base Data

Local Order Number 118-05850

Type T50SOS

Color Black (BK)

Features and Benefits The OS range of outside serrated cable ties offers high tensile strengths, low insertion force and a smooth surface to the cable - minimizing any indentation or damage to the insulation. The curved shape of the head allows the tie to follow the contours of the cable and takes up less space than other tie designs.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Outside Serrated

Short Description Outside Serrated Cable Ties, 50lb. 5.9" Max. Bun. Dia 1.38" PA66HS, Black, 100/pk

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225 N

Length L (imperial) 5.9 "

Length L (metric) 150 mm

Width W (imperial) 0.18 "

Width W (metric) 4.6 mm

Height H (imperial) 0.0512 "

Height H (metric) 1.3 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.6 mm

Bundle Diameter max (imperial) 1.38 "

Bundle Diameter max (metric) 35.0 mm

Thickness T (imperial) 0.05 "

Thickness T (Metric) 1.3 mm

Logistics and Packaging

Quantity per bag

Package Quantity 100

Carton Quantity 7000 Pieces

Weight (Metric) 1.2 kg

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-40 °F to +221 °F (-40 °C to +105 °C)
ROHS Conformity	Yes