

118-05900



Article Number: 118-05900

Outside Serrated Cable Tie, 15" Long, 50lb Tensile Strength, PA66HS, Black, 100/pkg



Base Data

Local Order Number 118-05900

Type T50LOS

Color Black (BK)

- Features and Benefits**
- Outside serrations minimize damage to cables, while still providing high tensile strength and low insertion force.
 - Contour style head design provides additional space in constrained areas.
 - Heat stabilized material provides excellent resistance to high heat exposures.

Product Description HellermannTyton outside serrated cable ties are designed with a smooth inside surface to help minimize indentation or damage to wire and cable insulation, while offering high tensile strength and low insertion force. The contour style head takes up less space than traditional style cable ties making it ideal for space constrained areas. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Outside Serrated

Short Description Outside Serrated Cable Tie, 15" Long, 50lb Tensile Strength, PA66HS, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225.0 N

Length L (imperial) 15.0 "

Length L (metric) 384.0 mm

Width W (imperial) 0.18 "

Width W (metric) 4.6 mm

Height H (imperial) 0.051 "

Height H (metric) 1.3 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.6 mm

Bundle Diameter max (imperial) 4.3 "

Bundle Diameter max (metric) 110.0 mm

Thickness T (imperial) 0.05 "

Cable Tie Head Height (Metric) 5.9 mm

Cable Tie Head Length (metric) 6.75 mm

Cable Tie Head Width (metric) 7.9 mm

Cable Tie Head Length (imperial) 0.26 "

Cable Tie Head Width (imperial) 0.31 "

Thickness T (Metric) 1.3 mm

Logistics and Packaging

Quantity per bag

Package Quantity 100

Carton Quantity 4000 Pieces

Weight (Metric) 4 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Halogenfree Yes

Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)

ROHS Conformity Yes