

121-83355

Article Number: 121-83355

Kabelrap Tie, 13.3" Long, 176lb Tensile Strength, PA66HS, Natural, 50/pkg



Base Data

Local Order Number 121-83355

Type KR8/33

Color Natural (NA)

Features and Benefits

- Kabelrap tie offers a smooth strap providing secure assembly without damaging cables or hoses.
- Curved head design provides full circumferential compression which offers vibration resistance.

Product Description The patented Kabelrap cable tie design offers a smooth strap which is locked into place with a glass fiber reinforced pin. The curved head design provides full circumferential compression around the bundle or harness. Once applied with the required KR6/8 manual tool, the tie offers a secure and vibration resistant assembly.

Fixation Method (FF) Connector Clip

Releasable Closure (Yes/No) No

Tie Closure fibreglass pin

Variant No Serration

Short Description Kabelrap Tie, 13.3" Long, 176lb Tensile Strength, PA66HS, Natural, 50/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 176.0 lbs

Minimum Tensile Strength (N) 785.0 N

Length L (imperial) 13.3 "

Length L (metric) 337.0 mm

Width W (imperial) 0.32 "

Width W (metric) 8.0 mm

Bundle Diameter min (imperial) 0.32 "

Bundle Diameter min (metric) 8.0 mm

Bundle Diameter max (imperial) 3.4 "

Bundle Diameter max (metric) 86.0 mm

Thickness T (imperial) 0.091 "

Cable Tie Head Height (Metric) 7.7 mm

Cable Tie Head Length (metric) 8.2 mm

Cable Tie Head Width (metric) 11.8 mm

Cable Tie Head Length (imperial) 0.31 "

Cable Tie Head Width (imperial) 0.46 "

Thickness T (Metric) 2.3 mm

Logistics and Packaging

Quantity per pc

Package Quantity 50
Carton Quantity 1500 Pieces
Weight (Metric) 4.43 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut PA66HS
Flammability UL94 V2
Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)
ROHS Conformity Yes