

126-00001

Article Number: 126-00001

Wing Push Mount Tie, 6" Long, 50lb Tensile, PA66HS, Black, 500/bag



Base Data

Local Order Number	126-00001
Type	T50SL5
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"><li>• Wing design helps stabilize the tie in high vibration applications</li><li>• Includes a ladder type strap as opposed to a conventional serrated strap; providing the benefit of being extra flexible.</li><li>• Design of tie provides low insertion and high extraction force.</li></ul>
Product Description	Wing Push Mount Ties' supporting legs ensure a firm and secure fixing for bundles. These legs also reduce vibration in panel thickness enabling one part to suit many different applications such as sheet metal, wood, and cast iron.
Fixation Method (FF)	Arrowhead
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Wing Push Mount Tie, 6" Long, 50lb Tensile, PA66HS, Black, 500/bag

Product Dimensions

Minimum Tensile Strength (imperial)	50.0 lbs
Minimum Tensile Strength (N)	222 N
Length L (imperial)	6.5 "
Length L (metric)	165 mm
Width W (imperial)	0.19 "
Width W (metric)	4.7 mm
Width W2 (imperial)	0.73 "
Width W2 (metric)	18.5 mm
Bundle Diameter min (imperial)	0.06 "
Bundle Diameter min (metric)	1.5 mm
Bundle Diameter max (imperial)	1.3 "
Bundle Diameter max (metric)	34.0 mm
Panel Thickness max. (imperial)	0.03 "
Panel Thickness max. (metric)	2.5 mm
Panel Thickness min. (imperial)	0.31 "
Panel Thickness min. (metric)	0.8 mm
Mounting Hole Diameter D (imperial)	0.24 - 0.26 "
Mounting Hole Diameter D (metric)	6.1 - 6.5 mm

<b>Mounting Hole Diameter D min (imperial)</b>	0.24 "	<b>Mounting Hole Diameter D max (imperial)</b>	0.255 "	<b>Thickness T (imperial)</b>	0.05 "
<b>Mounting Hole Diameter D max (metric)</b>	6.5 mm	<b>Mounting Hole Diameter D min (metric)</b>	6.1 mm		
<b>Thickness T (Metric)</b>	1.2 mm				

## Logistics and Packaging

<b>Quantity per</b>	pc
<b>Package Quantity</b>	500
<b>Carton Quantity</b>	4000 Pieces
<b>Weight (Metric)</b>	1.6 kg

## Material and Specifications

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +221 °F (-40 °C to +105 °C)
<b>ROHS Conformity</b>	Yes