

126-00005

Article Number: 126-00005

Wing Push Mount Tie, 6" Long, 50lb Tensile, PA66HIRHS, Black, 500/bag



Base Data

Local Order Number 126-00005

Type T50SL5

Color Black (BK)

Features and Benefits

- Wing design helps stabilize the tie in high vibration applications
- Includes a ladder type strap as opposed to a conventional serrated strap; providing the benefit of being extra flexible.
- Design of tie provides low insertion and high extraction force.

Product Description Wing Push Mount Ties' supporting legs ensure a firm and secure fixing for bundles. These legs also reduce vibration in panel thickness enabling one part to suit many different applications such as sheet metal, wood, and cast iron.

Fixation Method (FF) Arrowhead

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Wing Push Mount Tie, 6" Long, 50lb Tensile, PA66HIRHS, Black, 500/bag

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 222 N

Length L (imperial) 6.5 "

Length L (metric) 163 mm

Width W (imperial) 0.18 "

Width W (metric) 4.6 mm

Width W2 (imperial) 0.73 "

Width W2 (metric) 18.5 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.5 mm

Bundle Diameter max (imperial) 1.3 "

Bundle Diameter max (metric) 34.0 mm

Panel Thickness max. (imperial) 0.03 "

Panel Thickness max. (metric) 2.7 mm

Panel Thickness min. (imperial) 0.31 "

Panel Thickness min. (metric) 0.8 mm

Mounting Hole Diameter D (imperial) 0.24 - 0.26 "

Mounting Hole Diameter D (metric) 6.1 - 6.5 mm

Mounting Hole Diameter D min 0.24 "
(imperial)

Mounting Hole Diameter D max 0.255 "
(imperial)

Thickness T (imperial) 0.05 "

Mounting Hole Diameter D max 6.5 mm
(metric)

Mounting Hole Diameter D min (metric) 6.1 mm

Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity per bag

Package Quantity 500

Carton Quantity 4000 Pieces

Weight (Metric) 1.6 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL94 HB

Halogenfree Yes

Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)

ROHS Conformity Yes