


126-00015



Article Number: 126-00015

Domed Push Mount Tie, 6.3" Long, Fixing Hole Diameter .24" - .48", PA66HS, Black, 500/pkg

 RoHS

Base Data

Local Order Number	126-00015
Type	T50SDOP
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none">• Part is easy to install without the need for a tool.• Design provides low insertion and high extraction force.• The oval design helps prevent the part from twisting.
Product Description	HellermannTyton's dome push in tie with arrowhead locks into place between the fixing and the head of the cable tie. This covers the hole and minimizes the ingress of dust, dirt, and water. The anchor adjusts for variations in panel thickness, which ensures a secure fixing at all times. The oval design helps prevent the part from twisting.
Fixation Method (FF)	Arrowhead for oval holes
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Domed Push Mount Tie, 6.3" Long, Fixing Hole Diameter .24" - .48", PA66HS, Black, 500/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	50.0 lbs
Minimum Tensile Strength (N)	225 N
Length L (imperial)	6.3 "
Length L (metric)	160.0 mm
Width W (imperial)	0.2 "
Width W (metric)	5.0 mm
Height H (imperial)	0.36 "
Bundle Diameter min (imperial)	0.2 "
Bundle Diameter min (metric)	5.0 mm
Bundle Diameter max (imperial)	1.2 "
Bundle Diameter max (metric)	30.0 mm
Disc Diameter (imperial)	0.87 "
Disc Diameter (metric)	22.0 mm
Panel Thickness max. (imperial)	0.08 "
Panel Thickness max. (metric)	1.9 mm
Panel Thickness min. (imperial)	0.04 "
Panel Thickness min. (metric)	1.0 mm
Mounting Hole Diameter D (imperial)	0.24 - 0.48 "

Mounting Hole Diameter D (metric)	6.2 x 12.2 mm		
Mounting Hole Diameter D min (imperial)	0.244 "	Mounting Hole Diameter D max (imperial)	0.48 "
		Stud Length min (metric)	9.2 mm
Thickness T (imperial)	0.05 "		
Mounting Hole Diameter D max (metric)	12.2 mm	Mounting Hole Diameter D min (metric)	6.2 mm
Thickness T (Metric)	1.3 mm		

Logistics and Packaging

Quantity per	bag
Package Quantity	500
Carton Quantity	4000 Pieces
Weight (Metric)	1.7 kg

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2
Operating Temperature	-40 °F to +221 °F (-40 °C to +105 °C)
ROHS Conformity	Yes