

126-00042



Article Number: 126-00042

Arrowhead Wing Push Mount Tie, 4.5" Long, 18lb, Panel Thickness 0.19"- 0.22", PA66, Black, 1,000/pkg



Base Data

Local Order Number	126-00042
Type	T18RWPM
Color	Black (BK)
Features and Benefits	• Easy and quick insertion ideal for production environment. • Tie "clicks" into place upon final installation signaling installer insertion is complete. • Arrowhead style mount provides low insertion and high extraction force.
Product Description	Arrowhead Wing Push Ties design helps stabilize the tie in high vibration applications. This can be used on sheet metal, wood, and cast iron.
Fixation Method (FF)	Arrowhead
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Arrowhead Wing Push Mount Tie, 4.5" Long, 18lb, Panel Thickness 0.19"- 0.22", PA66, Black, 1,000/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	18.0 lbs
Minimum Tensile Strength (N)	80 N
Length L (imperial)	4.5 "
Length L (metric)	113.0 mm
Width W (imperial)	0.1 "
Width W (metric)	2.5 mm
Width W2 (imperial)	0.25 "
Width W2 (metric)	6.4 mm
Height H (imperial)	0.23 "
Height H (metric)	5.8 mm
Bundle Diameter min (imperial)	0.06 "
Bundle Diameter min (metric)	1.5 mm
Bundle Diameter max (imperial)	0.86 "
Bundle Diameter max (metric)	22.0 mm
Disc Diameter (imperial)	0.5 "
Disc Diameter (metric)	13.2 mm
Panel Thickness max. (imperial)	0.13 "
Panel Thickness max. (metric)	3.2 mm
Panel Thickness min. (imperial)	0.06 "

Panel Thickness min. (metric)	1.52 mm		
Mounting Hole Diameter D (imperial)	0.19 - 0.22 "		
Mounting Hole Diameter D (metric)	4.8 - 5.6 mm		
Mounting Hole Diameter D min (imperial)	0.19 "	Mounting Hole Diameter D max (imperial)	0.22 "
			Thickness T (imperial)0.043 "
Mounting Hole Diameter D max (metric)	5.6 mm	Mounting Hole Diameter D min (metric)	4.8 mm
Thickness T (Metric)	1.1 mm		

Logistics and Packaging

Quantity per	bag
Package Quantity	1000
Carton Quantity	10000

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2
Operating Temperature	-40 °F to +221 °F (-40 °C to +105 °C)
ROHS Conformity	Yes
Certification / Specification	UL