

126-00043

Article Number: 126-00043

Push Mount Tie, 6" Long, 50lb Tensile, Panel Thickness .04"-.14", PA66, Natural, 100/pkg



Base Data

Local Order Number 126-00043

Type T50SSF

Color Natural (NA)

- Features and Benefits**
- Quick and easy mounting will save time.
 - Tie is releasable and reusable providing a cost savings.
 - Design provides low insertion and high extraction force.

Product Description Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.

Fixation Method (FF) Arrowhead

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Push Mount Tie, 6" Long, 50lb Tensile, Panel Thickness .04"-.14", PA66, Natural, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225 N

Length L (imperial) 6.25 "

Length L (metric) 159.0 mm

Width W (imperial) 0.19 "

Width W (metric) 4.7 mm

Height H (imperial) 0.3 "

Height H (metric) 7.5 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.5 mm

Bundle Diameter max (imperial) 1.4 "

Bundle Diameter max (metric) 35.0 mm

Panel Thickness max. (imperial) 0.14 "

Panel Thickness max. (metric) 3.56 mm

Panel Thickness min. (imperial) 0.04 "

Panel Thickness min. (metric) 1.00 mm

Mounting Hole Diameter D min (imperial) 0.25 "

Mounting Hole Diameter D max0.28 "
(imperial)

Mounting Hole Diameter D max7.1 mm
(metric)

Mounting Hole Diameter D min (metric) 6.4 mm

Logistics and Packaging

Quantity per bag
Package Quantity 100
Carton Quantity 5000

Material and Specifications

Material Polyamide 6.6 (PA66)
Material Shortcut PA66
Flammability UL94 V2
Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity Yes