

126-00045



Article Number: 126-00045

Push Mount Tie, 6" Long, 50lb Tensile, Panel Thickness .04"-.14", PA66HS, Black, 100/pkg



Base Data

Local Order Number	126-00045
Type	T50SSF
Color	Black (BK)
Features and Benefits	• Quick and easy mounting will save time. • Tie is releasable and reusable providing a cost savings. • Design provides low insertion and high extraction force.
Product Description	Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.
Fixation Method (FF)	Arrowhead
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Push Mount Tie, 6" Long, 50lb Tensile, Panel Thickness .04"-.14", PA66HS, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	50.0 lbs
Minimum Tensile Strength (N)	225 N
Length L (imperial)	6.25 "
Length L (metric)	159.0 mm
Width W (imperial)	0.19 "
Width W (metric)	4.7 mm
Height H (imperial)	0.3 "
Height H (metric)	7.5 mm
Bundle Diameter min (imperial)	0.06 "
Bundle Diameter min (metric)	1.5 mm
Bundle Diameter max (imperial)	1.4 "
Bundle Diameter max (metric)	35.0 mm
Panel Thickness max. (imperial)	0.14 "
Panel Thickness max. (metric)	3.56 mm
Panel Thickness min. (imperial)	0.04 "
Panel Thickness min. (metric)	1.00 mm
Mounting Hole Diameter D min (imperial)	0.25 "
Mounting Hole Diameter D max (imperial)	0.28 "
Mounting Hole Diameter D max (metric)	7.1 mm

Mounting Hole Diameter D min (metric) 6.4 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	100
Carton Quantity	5000

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66HS
Flammability	UL94 V2
Operating Temperature	-40 °F to +221 °F (-40 °C to +105 °C)
ROHS Conformity	Yes