

126-00049



Article Number: 126-00049

Wing Push Mount Tie, 6.0" Long, 50lb Tensile, PA66HIRHS, Black, 500/bag



Base Data

Local Order Number 126-00049

Type T50SSFMM

Color Black (BK)

- Features and Benefits**
- Wing design helps stabilize the tie in high vibration applications.
 - Includes a ladder type strap as opposed to a conventional serrated strap; giving the benefit of being extra flexible.
 - Wing design provides low insertion and high extraction force.

Product Description Wing Push Mount Ties' supporting legs ensure a firm and secure fixing for bundles. These legs also reduce vibration in panel thickness enabling one part to suit many different applications such as sheet metal, wood, and cast iron.

Fixation Method (FF) Arrowhead

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Wing Push Mount Tie, 6.0" Long, 50lb Tensile, PA66HIRHS, Black, 500/bag

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225 N

Length L (imperial) 6.3 "

Length L (metric) 160.0 mm

Width W (imperial) 0.18 "

Width W (metric) 4.6 mm

Width W2 (imperial) 0.6 "

Width W2 (metric) 14.7 mm

Height H (imperial) 0.2 "

Height H (metric) 5.6 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.5 mm

Bundle Diameter max (imperial) 1.4 "

Bundle Diameter max (metric) 35.0 mm

Panel Thickness max. (imperial) 0.12 "

Panel Thickness max. (metric) 3.0 mm

Panel Thickness min. (imperial) 0.03 "

Panel Thickness min. (metric) 0.7 mm

Mounting Hole Diameter D (metric) 6.0 - 6.6 mm

Mounting Hole Diameter D min 0.24 "
(imperial)

Mounting Hole Diameter D max 0.25 "
(imperial)

Mounting Hole Diameter D max 6.6 mm
(metric)
6.0 mm

Mounting Hole Diameter D min (metric)

Logistics and Packaging

Quantity per bag
Package Quantity 500
Carton Quantity 5000

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut PA66HIRHS
Flammability UL94 HB
Operating Temperature -40 °F to +230 °F (-40 °C to +110 °C)
ROHS Conformity Yes