

126-00065

Article Number: 126-00065

Arrowhead Mount Ties with Seal, 6.5" Long, 50lb Tensile, PA66HS, Natural, 500/bag

HellermannTyton



Base Data

Local Order Number 126-00065

Type T50S0SSFT6.5E-MS-MD

Color Natural (NA)

- Features and Benefits**
- Arrowhead design is easy and quick install by hand without the need for tools.
 - Ties "clicks" into place upon final installation signaling installer insertion is complete .
 - Design provides low insertion and high extraction force.
 - Seal helps to prevent the ingress of water, dirt, or dust from getting through the mounting hole.

Product Description Arrowhead Push Ties with rubber seal secure fast and easy, while providing a special rubber seal to minimize water, dirt, or dust from getting through the mounting hole. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times.

Fixation Method (FF) Arrowhead

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Outside Serrated

Short Description Arrowhead Mount Ties with Seal, 6.5" Long, 50lb Tensile, PA66HS, Natural, 500/bag

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 180 N

Length L (imperial) 6.5 "

Length L (metric) 163.0 mm

Width W (imperial) 0.18 "

Width W (metric) 4.6 mm

Height H (imperial) 0.63 "

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.5 mm

Bundle Diameter max (imperial) 1.4 "

Bundle Diameter max (metric) 35.0 mm

Disc Diameter (imperial) 0.63 "

Disc Diameter (metric) 16.0 mm

Panel Thickness max. (imperial) 0.06 "

Panel Thickness max. (metric) 1.6 mm

Panel Thickness min. (imperial) 0.03 "

Panel Thickness min. (metric) 0.7 mm

Mounting Hole Diameter D (imperial)	0.25 - 0.27 "		
Mounting Hole Diameter D (metric)	6.25 - 6.75 mm		
Mounting Hole Diameter D min (imperial)	0.244 "	Mounting Hole Diameter D max (imperial)	0.26 "
			Thickness T (imperial) 0.05 "
Mounting Hole Diameter D max (metric)	6.75 mm	Mounting Hole Diameter D min (metric)	6.25 mm
Thickness T (Metric)	1.3 mm		

Logistics and Packaging

Quantity per	bag
Package Quantity	500
Carton Quantity	3000 Pieces
Weight (Metric)	1.51 kg

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2
Operating Temperature	-40 °F to +221 °F (-40 °C to +105 °C)
ROHS Conformity	Yes