

126-00081

Article Number: 126-00081



Base Data

Local Order Number	126-00081
Type	T50SOSKSFT65E
Color	Black (BK)
Features and Benefits	When inserted into the hole the arrowhead locks into place and the 'disc', between the fixing and the head of the cable tie, covers the hole and minimises the ingress of dust, dirt and water. The anchor will adjust for variations in panel thickness thereby ensuring a secure fixing at all times. The T50SST type has a small 'tab' placed below the head, which gives additional protection against axial forces and is particularly useful to assist retention on convoluted tubing.
Fixation Method (FF)	Arrowhead (Small Mount)
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Outside Serrated

Product Dimensions

Minimum Tensile Strength (imperial)	40.0 lbs
Minimum Tensile Strength (N)	180 N
Length L (imperial)	6.2 "
Length L (metric)	156.0 mm
Width W (imperial)	0.18 "
Width W (metric)	4.6 mm
Bundle Diameter min (imperial)	0.04 "
Bundle Diameter min (metric)	1.0 mm
Bundle Diameter max (imperial)	1.38 "
Bundle Diameter max (metric)	35.0 mm
Disc Diameter (imperial)	0.63 "
Disc Diameter (metric)	16.0 mm
Panel Thickness max. (imperial)	0.051 "
Panel Thickness max. (metric)	1.3 mm
Panel Thickness min. (imperial)	0.027 "
Panel Thickness min. (metric)	0.7 mm
Mounting Hole Diameter D (imperial)	0.25-0.26 "
Mounting Hole Diameter D min (imperial)	0.248 "
Mounting Hole Diameter D max (imperial)	0.264 "
Mounting Hole Diameter D max (metric)	6.7 mm

Mounting Hole Diameter D min (metric)

(metric)6.3 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	500
Carton Quantity	5000 Pieces
Weight (Metric)	1.3 kg

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2
Operating Temperature	-40 °F to +221 °F (-40 °C to +105 °C)
ROHS Conformity	Yes