

Article Number: 126-00099



## Base Data

**Local Order Number** 126-00099

**Type** T50SOSKSFT5SE

**Color** Black (BK)

**Features and Benefits** When inserted into the hole the arrowhead locks into place and the 'disc', between the fixing and the head of the cable tie, covers the hole and minimises the ingress of dust, dirt and water. The anchor will adjust for variations in panel thickness thereby ensuring a secure fixing at all times.  
The T50SST type has a small 'tab' placed below the head, which gives additional protection against axial forces and is particularly useful to assist retention on convoluted tubing.

**Fixation Method (FF)** Arrowhead

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Outside Serrated

## Product Dimensions

**Minimum Tensile Strength (imperial)** 40.0 lbs

**Minimum Tensile Strength (N)** 180 N

**Length L (imperial)** 6.2 "

**Length L (metric)** 156.0 mm

**Width W (imperial)** 0.18 "

**Width W (metric)** 4.6 mm

**Bundle Diameter min (imperial)** 0.04 "

**Bundle Diameter min (metric)** 1.0 mm

**Bundle Diameter max (imperial)** 1.38 "

**Bundle Diameter max (metric)** 35.0 mm

**Disc Diameter (imperial)** 0.63 "

**Disc Diameter (metric)** 16.0 mm

**Panel Thickness max. (imperial)** 0.051 "

**Panel Thickness max. (metric)** 1.3 mm

**Panel Thickness min. (imperial)** 0.027 "

**Panel Thickness min. (metric)** 0.7 mm

**Mounting Hole Diameter D (imperial)** 0.189-0.205 "

**Mounting Hole Diameter D (metric)** 4.8 - 5.2 mm

**Mounting Hole Diameter D min (imperial)** 0.189 "

**Mounting Hole Diameter D max** 0.205 "

(imperial)

Thickness T (imperial) 0.05 "

Mounting Hole Diameter D max (metric) 5.2 mm  
Mounting Hole Diameter D min (metric) 4.8 mm  
Thickness T (Metric) 1.3 mm

## Logistics and Packaging

---

Quantity per bag  
Package Quantity 1000  
Carton Quantity 6000 Pieces  
Weight (Metric) 1.5 kg

## Material and Specifications

---

Material Polyamide 6.6 heat stabilized (PA66HS)  
Material Shortcut PA66HS  
Flammability UL94 V2  
Minimum Extraction Force (Imperial) 40.0 lbs  
Minimum Extraction Force (Metric) 180 N  
Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)  
ROHS Conformity Yes