

126-00114

Article Number: 126-00114

Arrowhead Push Tie, 8.5" Long, 50lb, .07" - .12" Panel Thickness, PA66HIRHS, Natural, 500/pkg



Base Data

Local Order Number 126-00114

Type T50ROSAH6U

Color Natural (NA)

- Features and Benefits**
- Arrowhead style mount provides low insertion and high extraction force.
 - Easy and quick insertion ideal for production environment.
 - Ties "clicks" into place upon final installation signaling installer insertion is complete.

Product Description Arrowhead Push Ties secure fast and easy, while providing a disc feature to minimize the ingress of dust, dirt, and water. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times.

Fixation Method (FF) Arrowhead

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Outside Serrated

Short Description Arrowhead Push Tie, 8.5" Long, 50lb, .07" - .12" Panel Thickness, PA66HIRHS, Natural, 500/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225.0 N

Length L (imperial) 8.5 "

Length L (metric) 215.9 mm

Width W (imperial) 0.2 "

Width W (metric) 5.1 mm

Bundle Diameter max (imperial) 2.0 "

Bundle Diameter max (metric) 50.0 mm

Disc Diameter (imperial) 0.63 "

Disc Diameter (metric) 15.9 mm

Panel Thickness max. (imperial) 0.12 "

Panel Thickness max. (metric) 3.0 mm

Panel Thickness min. (imperial) 0.07 "

Panel Thickness min. (metric) 1.8 mm

Logistics and Packaging

Quantity per bag

Package Quantity 500

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Operating Temperature	-40 °F to +230 °F (-40 °C to +110 °C)
ROHS Conformity	Yes