

126-00116

Article Number: 126-00116

Wing Push Mount Tie, 8" Long, 50lb Tensile, PA66HS, Black, 500/bag

HellermannTyton



## Base Data

Local Order Number 126-00116

Type T50RSFM

Color Black (BK)

- Features and Benefits**
- Wing design helps stabilize the tie in high vibration applications.
  - Includes a ladder type strap as opposed to a conventional serrated strap which provides the benefit of being extra flexible.
  - Tie is releasable and reusable giving additional use options.

**Product Description** Wing Push Mount Ties' supporting legs ensure a firm and secure fixing for bundles. These legs also reduce vibration in panel thickness enabling one part to suit many different applications such as sheet metal, wood, and cast iron.

**Fixation Method (FF)** Arrowhead

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Wing Push Mount Tie, 8" Long, 50lb Tensile, PA66HS, Black, 500/bag

## Product Dimensions

**Minimum Tensile Strength (imperial)** 50.0 lbs

**Minimum Tensile Strength (N)** 225 N

**Length L (imperial)** 8.0 "

**Length L (metric)** 200.0 mm

**Width W (imperial)** 0.18 "

**Width W (metric)** 4.6 mm

**Height H (imperial)** 0.22 "

**Height H (metric)** 5.6 mm

**Bundle Diameter min (imperial)** 0.06 "

**Bundle Diameter min (metric)** 1.5 mm

**Bundle Diameter max (imperial)** 1.8 "

**Bundle Diameter max (metric)** 45.0 mm

**Panel Thickness max. (imperial)** 0.12 "

**Panel Thickness max. (metric)** 3.0 mm

**Panel Thickness min. (imperial)** 0.04 "

**Panel Thickness min. (metric)** 0.7 mm

**Mounting Hole Diameter D (imperial)** 0.24 -0.26 "

**Mounting Hole Diameter D (metric)** 6.0 - 6.6 mm

Mounting Hole Diameter D min (imperial) 0.24 "

Mounting Hole Diameter D max (imperial) 0.26 "

Thickness T (imperial) 0.05 "

Mounting Hole Diameter D max (metric) 6.6 mm

Mounting Hole Diameter D min (metric) 6.0 mm

Thickness T (Metric) 1.3 mm

---

## Logistics and Packaging

Quantity per bag

Package Quantity 500

Carton Quantity 4000

---

## Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)

ROHS Conformity Yes