

126-03100



Article Number: 126-03100

Arrowhead Mount Ties with Seal, 6.3" Long, 50lb Tensile, PA66HS, Green, 500/bag



Base Data

Local Order Number 126-03100

Type T50SOSSFT6.5E-MDL

Color Green (GN)

- Features and Benefits**
- Arrowhead design makes installation quick and easy by hand.
 - Ties "clicks" into place upon final installation signaling installer insertion is complete.
 - Design provides low insertion and high extraction force.

Product Description Arrowhead Push Ties with rubber seal secure fast and easy, while providing a special rubber seal to minimize water, dirt, or dust from getting through the mounting hole. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times.

Fixation Method (FF) Arrowhead

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Outside Serrated

Short Description Arrowhead Mount Ties with Seal, 6.3" Long, 50lb Tensile, PA66HS, Green, 500/bag

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 200 N

Length L (imperial) 6.3 "

Length L (metric) 158.8 mm

Length of Fir Tree 7.0 mm

Width W (imperial) 0.18 "

Width W (metric) 4.6 mm

Height H (imperial) 0.67 "

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.5 mm

Bundle Diameter max (imperial) 1.2 "

Bundle Diameter max (metric) 30.0 mm

Disc Diameter (imperial) 0.63 "

Disc Diameter (metric) 16.0 mm

Panel Thickness max. (imperial) 0.07 "

Panel Thickness max. (metric) 1.8 mm

Panel Thickness min. (imperial) 0.02 "

Panel Thickness min. (metric) 0.6 mm

Mounting Hole Diameter D (imperial) 0.25 - 0.26 "

Mounting Hole Diameter D min (imperial) 0.25 "

Mounting Hole Diameter D max (imperial) 0.26 "

Thickness T (imperial) 0.05 "

Mounting Hole Diameter D max (metric) 6.7 mm

Mounting Hole Diameter D min (metric) 6.3 mm

Thickness T (Metric) 1.3 mm

Logistics and Packaging

Quantity per bag

Package Quantity 500

Carton Quantity 3000 Pieces

Weight (Metric) 2 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)

ROHS Conformity Yes