HellermannTyton

132-00010



Article Number: 132-00010

Button Head Tie, 105lb, 9.6" Long, Max Bundle Diameter 2.6", PA66HSUV, Black, 50/pkg

Base Data

Local Order Number	132-00010
Туре	BT105R
Color	Black (BK)
Features and Benefits	 Unique two piece tie allows parallel entry and exit through the head for easy assembly. PA66HIRHS material make it ideal for trucking and heavy equipment applications.
Product Description	The button head tie is a two piece tie providing for parallel entry and exit through the head. The strap contains serrations on both sides, and has two opposed pawls recessed within a domed head. This design allows the strap to be directed clockwise or counter-clockwise prior to insertion into the head, enabling bi-directional looping.
Fixation Method (FF)	Connector Clip
Tie Closure	plastic pawl
Variant	Outside Serrated
Short Description	Button Head Tie, 105lb, 9.6" Long, Max Bundle Diameter 2.6", PA66HSUV, Black, 50/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	105.0 lbs
Minimum Tensile Strength (N)	467 N
Length L (imperial)	9.6 "
Length L (metric)	244.4 mm
Width W (imperial)	0.2 "
Width W (metric)	5.6 mm
Bundle Diameter min (imperial)	0.06 "
Bundle Diameter min (metric)	1.5 mm
Bundle Diameter max (imperial)	2.6 "
Bundle Diameter max (metric)	66.7 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	50
Carton Quantity	1000

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Material Cable Tie	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Flammability	UL94 HB

Material Head Polyamide 6.6 heat stabilized (PA66HS)

Operating Temperature -65 °F to +212 °F (-54 °C to +100 °C)

© HellermannTyton 2014