

148-00088

Article Number: 148-00088

Wire Clamping Cable Ties, Version A, Diameter Attachment .07", 6.0" Long, Black, PA66HS, 500/pkg



## Base Data

Local Order Number 148-00088

Type T50SOSWA2.0E

Color Black (BK)

- Features and Benefits**
- Clamp provides low insertion and high extraction force.
  - Various sizes available to accommodate all different sizes of bundles.
  - Clamp can be installed both before and after installation of bundles.

**Product Description** Wire Clamping Cable Ties secure easily to wire frames for a tight fit and are available in four different wire frame sizes and two separate orientations to provide both perpendicular and parallel routing. The wire clamp design is ideally suited for easing the application process on the production floor by allowing for an easy snap fit of the harness assembly to the wire frame.

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Short Description Wire Clamping Cable Ties, Version A, Diameter Attachment .07", 6.0" Long, Black, PA66HS, 500/pkg

## Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225 N

Length L (imperial) 6.0 "

Length L (metric) 150.0 mm

Attaches to Diameter (imperial) 0.08 "

Width W (imperial) 0.18 "

Width W (metric) 4.6 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.6 mm

Bundle Diameter max (imperial) 1.4 "

Bundle Diameter max (metric) 35.0 mm

Diameter D2 (imperial) 0.07 "

Nominal Diameter (imperial) 0.09 "

Nominal Diameter (metric) 2.0 mm

Thickness T (imperial) 0.05 "

Attaches to Diameter (metric) 2.0

Thickness T (Metric) 1.3

## Logistics and Packaging

Quantity per bag

**Package Quantity** 500

**Carton Quantity** 4000 Pieces

## **Material and Specifications**

---

**Material** Polyamide 6.6 heat stabilized (PA66HS)

**Material Shortcut** PA66HS

**Operating Temperature** -40 °F to +221 °F (-40 °C to +105 °C)

**ROHS Conformity** Yes