

148-00092

Article Number: 148-00092

Wire Clamping Cable Ties, Version A, Diameter Attachment .17", 6.0" Long, Black, PA66HS, 500/pkg



Base Data

Local Order Number 148-00092

Type T50SOSWA4.3E

Color Black (BK)

- Features and Benefits**
- Clamp provides low insertion and high extraction force.
 - Various sizes available to accommodate all different sizes of bundles.
 - Clamp can be installed both before and after installation of bundles.

Product Description Wire Clamping Cable Ties secure easily to wire frames for a tight fit and are available in four different wire frame sizes and two separate orientations to provide both perpendicular and parallel routing. The wire clamp design is ideally suited for easing the application process on the production floor by allowing for an easy snap fit of the harness assembly to the wire frame.

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Short Description Wire Clamping Cable Ties, Version A, Diameter Attachment .17", 6.0" Long, Black, PA66HS, 500/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225 N

Length L (imperial) 6.0 "

Length L (metric) 150.0 mm

Attaches to Diameter (imperial) 0.17 "

Width W (imperial) 0.18 "

Width W (metric) 4.6 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.6 mm

Bundle Diameter max (imperial) 1.4 "

Bundle Diameter max (metric) 35.0 mm

Diameter D (imperial) 0.17 "

Nominal Diameter (imperial) 0.17 "

Nominal Diameter (metric) 3.4 mm

Thickness T (imperial) 0.05 "

Attaches to Diameter (metric) 4.3

Thickness T (Metric) 1.3

Logistics and Packaging

Quantity per bag

Package Quantity 500

Carton Quantity 4000 Pieces

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

ROHS Conformity Yes