

150-00604

Article Number: 150-00604

Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter 0.25" - 0.28", PA66HS, Black, 7,000/pkg



Base Data

Local Order Number 150-00604

Type T30RFT6SDSET

Color Black (BK)

- Features and Benefits**
- Fir tree design can be used with a wide variety of applications.
 - Disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.
 - Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.

Product Description HellermannTyton's fir tree mounts provide a secure grip in a mounting hole and protect against dirt and other impurities. The mount can slide along the strap of the cable tie for proper orientation. The fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.

Fixation Method (FF) Fir Tree

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter 0.25" - 0.28", PA66HS, Black, 7,000/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 30.0 lbs

Length L (imperial) 6.0 "

Length L2 (imperial) 0.46 "

Length L2 (metric) 11.6 mm

Length of Fir Tree 7.5 mm

Width W (imperial) 0.14 "

Width W2 (imperial) 0.4 "

Height H (imperial) 0.04 "

Height H2 (imperial) 0.3 "

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter max (imperial) 1.4 "

Disc Diameter (imperial) 0.63 "

Disc Diameter (metric) 16.0 mm

Panel Thickness max. (imperial) 0.12 "

Panel Thickness min. (imperial) 0.03 "

Mounting Hole Diameter D (imperial) 0.26 - 0.28 "

Logistics and Packaging

| | |
|-------------------------|-------------|
| Quantity per | carton |
| Package Quantity | 7000 |
| Carton Quantity | 7000 Pieces |
| Weight (Metric) | 1.5 kg |

Material and Specifications

| | |
|------------------------------|---|
| Material | Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HS PA66HIRHS |
| Operating Temperature | -40 °F to +221 °F (-40 °C to +105 °C) |
| ROHS Conformity | Yes |