

150-09201



Article Number: 150-09201

Bundling Clip, .8" Length, Panel Thickness 0.25"- 0.28", PA66, Brown, 500/pkg



Base Data

Local Order Number 150-09201

Type COW20DP7

Color Brown (BN)

- Features and Benefits**
- Clip can be installed by hand without the need for a tool.
 - Design provides low insertion force and high extraction force ideal for the production environment.
 - Clip secures bundle away from areas that can cause rubbing and chafing.

Product Description Bundling clips are designed to provide simple and easy methods of securing cable bundles, hoses, or pipes. They are fastened onto the tape bar using tape or cable ties. The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters. Standard bundling clips are available as well as standoff and stud mount versions.

Fixation Method (FF) Fir Tree

Short Description Bundling Clip, .8" Length, Panel Thickness 0.25"- 0.28", PA66, Brown, 500/pkg

Product Dimensions

Length L (imperial) 0.8 "

Length L (metric) 20.0 mm

Width W (imperial) 1.7 "

Width W (metric) 42.0 mm

Height H (imperial) 0.26 "

Height H (metric) 6.6 mm

Panel Thickness max. (imperial) 0.18 "

Panel Thickness max. (metric) 4.5 mm

Panel Thickness min. (imperial) 0.03 "

Panel Thickness min. (metric) 0.8 mm

Mounting Hole Diameter D (imperial) 0.25 - 0.28 "

Mounting Hole Diameter D (metric) 6.3 - 7.0 mm

Mounting Hole Diameter D min (imperial) 0.25 "

Mounting Hole Diameter D max 0.275 " (imperial)

Mounting Hole Diameter D max 7.0 mm (metric)
6.3 mm

Mounting Hole Diameter D min (metric)

Logistics and Packaging

Quantity per bag

Package Quantity 500

Carton Quantity 4000 Pieces

Weight (Metric) 1.5 kg

Material and Specifications

| | |
|------------------------------|--------------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL94 V2 |
| Operating Temperature | -40 °F to +185 °F (-40 °C to +85 °C) |
| ROHS Conformity | Yes |