

150-55610



Article Number: 150-55610

Fir Tree with Tie, 4.3" Long, Mounting Hole Diameter .19"-.20", PA46, Black, 500/pkg



## Base Data

Local Order Number 150-55610

Type T18RDP5

Color Black (BK)

**Features and Benefits**

- Fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation.
- Fir Tree design provides low extraction and high extraction force.

**Product Description** Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. This is sold as an assembly with the cable tie.

Fixation Method (FF) Fir Tree

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Fir Tree with Tie, 4.3" Long, Mounting Hole Diameter .19"-.20", PA46, Black, 500/pkg

## Product Dimensions

Minimum Tensile Strength (imperial) 18.0 lbs

Minimum Tensile Strength (N) 80 N

Length L (imperial) 4.3 "

Length L (metric) 110.0 mm

Length of Fir Tree 7.8 mm

Width W (imperial) 0.1 "

Width W (metric) 2.5 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.5 mm

Bundle Diameter max (imperial) 0.8 "

Bundle Diameter max (metric) 20.0 mm

Disc Diameter (imperial) 0.5 "

Disc Diameter (metric) 13.0 mm

Panel Thickness max. (imperial) 0.02 "

Panel Thickness max. (metric) 4.0 mm

Panel Thickness min. (imperial) 0.12 "

Panel Thickness min. (metric) 3.0 mm

Mounting Hole Diameter D (imperial) 0.19 - 0.2 "

Mounting Hole Diameter D (metric) 4.9 - 5.1 mm

<b>Mounting Hole Diameter D min (imperial)</b>	0.19 "	<b>Mounting Hole Diameter D max (imperial)</b>	0.197 "	<b>Thickness T (imperial)</b>	0.043 "
<b>Mounting Hole Diameter D max (metric)</b>	5.1 mm	<b>Mounting Hole Diameter D min (metric)</b>	4.9 mm		
<b>Thickness T (Metric)</b>	1.1 mm				

## Logistics and Packaging

---

<b>Quantity per</b>	pc
<b>Package Quantity</b>	500
<b>Carton Quantity</b>	12000 Pieces
<b>Weight (Metric)</b>	0.6 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes