

150-74890

Article Number: 150-74890

Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter 0.23" - 0.24", PA66HS, Black, 500/pkg

HellermannTyton



Base Data

Local Order Number 150-74890

Type T30RFT6D10

Color Black (BK)

Features and Benefits

- Fir tree design can be used with a wide variety of applications.
- Disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.
- Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.

Product Description HellermannTyton's fir tree mounts provide a secure grip in a mounting hole and protect against dirt and other impurities. The mount can slide along the strap of the cable tie for proper orientation. The fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.

Fixation Method (FF) Fir Tree

Identification Plate Position none

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter 0.23" - 0.24", PA66HS, Black, 500/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 30.0 lbs

Minimum Tensile Strength (N) 135 N

Length L (imperial) 6.0 "

Length L (metric) 150 mm

Length L2 (imperial) 0.39 "

Length L2 (metric) 9.8 mm

Width W (imperial) 0.14 "

Width W (metric) 3.6 mm

Width W2 (imperial) 0.4 "

Height H (imperial) 0.04 "

Height H (metric) 1.1 mm

Height H2 (imperial) 0.4 "

Height H2 (metric) 9.5 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter max (imperial) 1.2 "

Bundle Diameter max (metric) 31.0 mm

Disc Diameter (imperial) 0.63 "

Disc Diameter (metric) 9.8 mm

Panel Thickness max. (imperial)	0.12 "		
Panel Thickness max. (metric)	4.3 mm		
Panel Thickness min. (imperial)	0.03 "		
Panel Thickness min. (metric)	0.8 mm		
Mounting Hole Diameter D (imperial)	0.23 - 0.24 "		
Mounting Hole Diameter D (metric)	5.8 - 6.2 mm		
Mounting Hole Diameter D min (imperial)	0.25 "		
		Mounting Hole Diameter D max0.27 "	
		(imperial)	Mounting Hole Diameter D max6.2 mm
			(metric) 5.8 mm
Mounting Hole Diameter D min (metric)			

Logistics and Packaging

Quantity per	bag
Package Quantity	500
Carton Quantity	5000 Pieces
Weight (Metric)	2 kg

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS PA66HIRHS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Material Edge Clip	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Flammability	UL94 HB
Operating Temperature	-40 °F to +221 °F (-40 °C to +105 °C)
ROHS Conformity	Yes