



151-00018



Article Number: 151-00018

Convoluted Tubing Clip, Max Bundle Diameter .4", Panel Thickness .03"-.24", PA66HIRHS, Black, 500/pkg

 **RoHS**

Base Data

Local Order Number	151-00018
Type	CTC10FT6LG
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none">• Clip includes an internal rib that spans the inside of the bracket to fit securely into the profile of the tubing to prevent lateral movement and slipping of the tubing.• Extended fir tree allows for a wide range of panel thicknesses.• Fir tree design provides low insertion forces and high extraction forces.
Product Description	Convoluted Tube Clips provide a quick and easy method for firmly securing corrugated covered cables and wires to a surface. Applications such as this can be found in a wide variety of industries such as the wire harness, automotive, trucking, and heavy equipment manufacturing industries.
Fixation Method (FF)	Fir Tree
Short Description	Convoluted Tubing Clip, Max Bundle Diameter .4", Panel Thickness .03"-.24", PA66HIRHS, Black, 500/pkg

Product Dimensions

Width W (imperial)	0.31 "
Width W (metric)	8.0 mm
Height H (imperial)	0.85 "
Height H (metric)	21.4 mm
Height H2 (imperial)	0.44 "
Height H2 (metric)	11.1 mm
Disc Diameter (imperial)	0.63 "
Disc Diameter (metric)	16.0 mm
Panel Thickness max. (imperial)	0.03 "
Panel Thickness max. (metric)	6.0 mm
Panel Thickness min. (imperial)	0.04 "
Panel Thickness min. (metric)	0.75 mm
Mounting Hole Diameter D (imperial)	0.26 - 0.28 "
Mounting Hole Diameter D (metric)	6.5 - 7.0 mm
Mounting Hole Diameter D min (imperial)	0.283 "
	Mounting Hole Diameter D max0.275 "
	(imperial)
	Nominal Diameter (imperial)0.39 "
Nominal Diameter (metric)	10.0 mm
Mounting Hole Diameter D max (metric)	7.0 mm
	Mounting Hole Diameter D min (metric)6.5 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	500
Carton Quantity	5000 Pieces
Weight (Metric)	1 kg

Material and Specifications

Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Operating Temperature	-40 °F to +221 °F (-40 °C to +105 °C)
ROHS Conformity	Yes