

151-00651



Article Number: 151-00651

Bundling Clip, Hole Diameter 6.2 - 6.8mm, Panel 0.7 - 18.0mm, PA66HIRHSUV, Natural, 2000/box

 RoHS

Base Data

Local Order Number	151-00651
Type	TC6FT6LG
Color	Natural (NA)
Features and Benefits	• Staggered fir tree branch design provides low insertion forces and high extraction forces for easy assembly. • Initial fir tree serves as a locating feature for assistance in blind assembly applications.
Product Description	HellermannTyton's Bundling Clip includes an extended fir tree mount to allow for a wide panel thickness range (0.7 - 18.0 mm). Anti-sliding bars on the ends of the connection bar assist in preventing the cable ties or tape from sliding off the clip in high movement/vibration applications.
Fixation Method (FF)	Fir Tree
Short Description	Bundling Clip, Hole Diameter 6.2 - 6.8mm, Panel 0.7 - 18.0mm, PA66HIRHSUV, Natural, 2000/box

Product Dimensions

Length L (imperial)	1.5 "
Length L (metric)	38.1 mm
Width W (imperial)	0.5 "
Width W (metric)	12.0 mm
Height H (imperial)	1.0 "
Height H (metric)	26.6 mm
Height H2 (imperial)	0.9 "
Height H2 (metric)	23.1 mm
Panel Thickness max. (imperial)	0.71 "
Panel Thickness max. (metric)	18.0 mm
Panel Thickness min. (imperial)	0.03 "
Panel Thickness min. (metric)	0.7 mm
Mounting Hole Diameter D (imperial)	0.26 "
Mounting Hole Diameter D (metric)	6.5 mm
Mounting Hole Diameter D min (imperial)	0.24 "
Mounting Hole Diameter D max (imperial)	0.24 "
Mounting Hole Diameter D min (metric)	6.2 mm
Mounting Hole Diameter D max (metric)	6.8 mm

Logistics and Packaging

Quantity per	box
Package Quantity	2000
Carton Quantity	2000

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Operating Temperature	-40 °F to +230 °F (-40 °C to +110 °C)
ROHS Conformity	Yes