

151-00663

Article Number: 151-00663

Bundling Clip, Hole Diameter 6.2 - 6.8mm, Panel 0.7 - 5.7mm, PA66HIRHSUV, Black, 2000/box



Base Data

Local Order Number 151-00663

Type TC6FT6

Color Black (BK)

Features and Benefits

- Staggered fir tree branch design provides low insertion forces and high extraction forces for easy assembly.
- Initial fir tree serves as a locating feature for assistance in blind assembly applications.

Product Description HellermannTyton's Bundling Clip includes an extended fir tree mount to allow for a wide panel thickness range (0.7 - 18.0 mm). Anti-sliding bars on the ends of the connection bar assist in preventing the cable ties or tape from sliding off the clip in high movement/vibration applications.

Fixation Method (FF) Fir Tree

Short Description Bundling Clip, Hole Diameter 6.2 - 6.8mm, Panel 0.7 - 5.7mm, PA66HIRHSUV, Black, 2000/box

Product Dimensions

Length L (imperial) 1.5 "

Length L (metric) 38.1 mm

Width W (imperial) 0.5 "

Width W (metric) 12.0 mm

Height H (imperial) 0.5 "

Height H (metric) 14.0 mm

Height H2 (imperial) 0.4 "

Height H2 (metric) 10.5 mm

Panel Thickness max. (imperial) 0.71 "

Panel Thickness max. (metric) 5.7 mm

Panel Thickness min. (imperial) 0.03 "

Panel Thickness min. (metric) 0.7 mm

Mounting Hole Diameter D (imperial) 0.26 "

Mounting Hole Diameter D (metric) 6.5 mm

Mounting Hole Diameter D min (imperial) 0.24 "

Mounting Hole Diameter D max 0.27 " (imperial)

Mounting Hole Diameter D max 6.2 mm (metric)
6.8 mm

Mounting Hole Diameter D min (metric)

Logistics and Packaging

Quantity per box

Package Quantity 2000

Carton Quantity 2000

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHSUV
Flammability	UL94 HB
Operating Temperature	-40 °F to +230 °F (-40 °C to +110 °C)