

151-00756



Article Number: 151-00756

High Torque Double Mnt, 4-Way, Mounting Hole .375", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg



## Base Data

<b>Local Order Number</b>	151-00756
<b>Type</b>	HDM375BDM4W
<b>Color</b>	Black (BK)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Arched "H" profile surface allows for broad surface contact with the bundle, minimizing pinching and crushing of the bundles.</li> <li>• High Torque metal bushing allows for strength in heavy duty applications.</li> <li>• These mounts contain a small tab inside the mounting hole to temporarily engage the threads which allows assemblers to pre-install the mount on a stud with a washer and nut.</li> </ul>
<b>Product Description</b>	High Torque Double Mounts are designed for routing multiple bundles with HellermannTyton heavy duty T250, T255, and wide strap cable ties to harness wires and hoses; however, they accept all standard cable ties up to .5" wide.
<b>Fixation Method (FF)</b>	Screw Mounting and Rivet
<b>Short Description</b>	High Torque Double Mnt, 4-Way, Mounting Hole .375", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg

## Product Dimensions

<b>Width W (imperial)</b>	1.4 "
<b>Width W (metric)</b>	34.5 mm
<b>Cable Tie Width Max (imperial)</b>	0.5 "
<b>Cable Tie Width max. (metric)</b>	12.7 mm
<b>Height H (imperial)</b>	1.0 "
<b>Height H (metric)</b>	25.2 mm
<b>Mounting Hole Diameter D (imperial)</b>	0.4 "
<b>Mounting Hole Diameter D (metric)</b>	9.5 mm

## Logistics and Packaging

<b>Quantity per</b>	bag
<b>Package Quantity</b>	100

## Material and Specifications

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40 °F to +221 °F (-40 °C to +105 °C)
<b>ROHS Conformity</b>	Yes

