

151-00785



Article Number: 151-00785



Base Data

Local Order Number 151-00785

Type CCFT6LG

Color Black (BK)

Features and Benefits The cable bundle is fastened to the winder bar with cable ties or adhesive tape. It is routed above the connector clip.

The two TapeClip elements are used to clip connectors onto the cable set. The connector is fixed securely to the set and is protected against soiling. None of the elements are direction-specific.

Fixation Method (FF) Fir Tree

Product Dimensions

Panel Thickness max. (imperial) 0.16 "

Panel Thickness max. (metric) 4.0 mm

Panel Thickness min. (imperial) 0.03 "

Panel Thickness min. (metric) 0.7 mm

Mounting Hole Diameter D (imperial) 0.24-0.26 "

Mounting Hole Diameter D (metric) 6.0 - 6.7 mm

Mounting Hole Diameter D min

(imperial)

Mounting Hole Diameter D max0.26 "

(imperial)

Mounting Hole Diameter D max6.7 mm

(metric)6.0 mm

Mounting Hole Diameter D min (metric)

Logistics and Packaging

Quantity per bag

Package Quantity 5000

Carton Quantity 5000 Pieces

Weight (Metric) 0.8 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL94 HB

Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)

ROHS Conformity Yes

