

151-00810



Article Number: 151-00810

Acrylic Adh. Bases, .18" Max tie width, 1.12" Length/Width, .18" Hole Dia., PA66UV, Black, 100/pkg



## Base Data

Local Order Number 151-00810

Type MB4A

Color Black (BK)

**Features and Benefits**

- For use with 18 and 50 pound cable ties to provide stability when securing bundles.
- The UV stabilized mounts and VHB acrylic adhesive resists UV light and seals against moisture and environmental conditions, while providing strong bond to the surface.
- 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

**Product Description** HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

**Fixation Method (FF)** Screw Mounting and Adhesive

**Short Description** Acrylic Adh. Bases, .18" Max tie width, 1.12" Length/Width, .18" Hole Dia., PA66UV, Black, 100/pkg

## Product Dimensions

Length L (imperial) 1.12 "

Length L (metric) 28.5 mm

Width W (imperial) 1.12 "

Width W (metric) 28.5 mm

Cable Tie Width Max (imperial) 0.18 "

Cable Tie Width max. (metric) 4.6 mm

Height H (imperial) 0.23 "

Height H (metric) 5.8 mm

Mounting Hole Diameter D (imperial) 0.18 "

Mounting Hole Diameter D (metric) 4.6 mm

Mounting Hole Centers (imperial) 0.8 "

Mounting Hole Centers (metric) 20.2 mm

## Logistics and Packaging

Quantity per bag

Package Quantity 100

## Material and Specifications

**Material** Polyamide 6.6 UV-stabilized (PA66UV)

**Material Shortcut** PA66UV

**Flammability** UL94 V2 (excluding adhesive)

**Operating Temperature** -40 °F to +185 °F (-40 °C to +85 °C)

**ROHS Conformity** Yes

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes