# HellermannTyton

#### 151-00973

Article Number: 151-00973

H-Mount for 0.375" standard bolts and Huck-Spin bolts, PA66HIRHSUV, Black, 900/pkg



RoHS

#### **Base Data**

Local Order Number 151-00973

Type HM4

Color Black (BK)

Features and Benefits • H-Mounts utilize existing frame rail bolts eliminating the need for additional fasteners.

· When used with cable ties, the H-Mounts eliminate the need to carry multiple sizes of fixed bundle diameter

clamps which reduces inventory and purchasing costs.

• Ability to position bundles in up to three locations, provides multiple use options.

Product Description H-mounts offer a secure bundling solution that utilizes existing frame rail bolts which reduces component costs and

improves installation time. The H-mounts have three bundle mounting locations each accommodating ties up to 1/2" wide. The top tie slot allows the bundle to be positioned directly over the bolt. The two curved tie slots on the sides

position the bundles adjacent to the bolt yet away from the frame.

Fixation Method (FF) thread-bolt

Short Description H-Mount for 0.375" standard bolts and Huck-Spin bolts, PA66HIRHSUV, Black, 900/pkg

### **Product Dimensions**

Length L (imperial) 2.0 "

Length L (metric) 50.0 mm

Width W (imperial) 1.0 "

Width W (metric) 26.0 mm

Cable Tie Width Max (imperial) 0.052 "

Cable Tie Width max. (metric) 13.2 mm

Height H (imperial) 1.1 "

Height H (metric) 28.0 mm

Stud Size (Imperial) 0.625 "

Stud Size (Metric) 15.9 mm

## **Logistics and Packaging**

Quantity per bag

Package Quantity 900

Carton Quantity 900

### **Material and Specifications**

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

CSA Certified No

Flammability UL94 HB

**Operating Temperature** -65 °F to +212 °F (-54 °C to +100 °C)

ROHS Conformity Yes

UL Listed (US and Canada) No

UL Listed (US) No

UL Recognized (US) No