# HellermannTyton

## 151-01166



Article Number: 151-01166

Locking Omega Clip, 10-14mm, with FT6 Fir Tree, PA66HIRHS, Black, 2000/ctn

#### **Base Data**

Local Order Number 151-01166

Type LOC1014FT6LG

Color Black (BK)

Features and Benefits • The 360 degree enclosure ensures the entire bundle is secure when being routed by this clip.

· Locking tab on this clip is small enough that it will not interfere with any other portion of the wire routing, but is

significant enough to allow for manual disengagement if service is needed. • The round 6mm fir free creates a secure fixating point within a panel.

• Disc around the fir tree eliminates the waste and water to enter the panel hole.

Product Description The Locking Omega Clip creates a full and secure lock completely around a wire bundle ranging from 10-14mm. The

fixating fir tree on this clip allows for the clip to be secured into a panel by a 6mm round hole.

Fixation Method (FF) Fir Tree

Short Description Locking Omega Clip, 10-14mm, with FT6 Fir Tree, PA66HIRHS, Black, 2000/ctn

#### **Product Dimensions**

Length L (imperial) 2.27 "

Length L (metric) 57.75 mm

Width W (imperial) 0.47 "

Width W (metric) 12.0 mm

Bundle Diameter min (imperial) 0.4 "

Bundle Diameter min (metric) 10.0 mm

Bundle Diameter max (imperial) 0.55 "

Bundle Diameter max (metric) 14.0 mm

Panel Thickness max. (imperial) 0.3 "

Panel Thickness max. (metric) 8.25 mm

Panel Thickness min. (imperial) 0.02 "

Panel Thickness min. (metric) 0.6 mm

Mounting Hole Diameter D (imperial) 0.25 "

Mounting Hole Diameter D (metric) 6.5 mm

### **Logistics and Packaging**

Quantity per box

Package Quantity 2000

## Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS

© HellermannTyton 2014