

151-02901

Article Number: 151-02901

Bundling Clip, 2.1" Length, Fixing Hole Diameter 0.26" - 0.28", PA66, Black, 500/pkg



## Base Data

Local Order Number 151-02901

Type CHA2

Color Black (BK)

- Features and Benefits**
- Clip can be installed by hand without the need for a tool.
  - Design provides low insertion force and high extraction force ideal for the production environment.
  - Clip secures bundle away from areas that can cause rubbing and chafing.

**Product Description** Bundling clips are designed to provide simple and easy methods of securing cable bundles, hoses, or pipes. They are fastened onto the tape bar using tape or cable ties. The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters. Standard bundling clips are available as well as standoff and stud mount versions.

Fixation Method (FF) Fir Tree

Short Description Bundling Clip, 2.1" Length, Fixing Hole Diameter 0.26" - 0.28", PA66, Black, 500/pkg

## Product Dimensions

Length L (imperial) 2.1 "

Length L (metric) 54.0 mm

Length of Fir Tree 8.0 mm

Width W (imperial) 0.24 "

Width W (metric) 6.0 mm

Height H (imperial) 0.3 "

Height H (metric) 7.7 mm

Height H2 (imperial) 0.32 "

Height H2 (metric) 8.0 mm

Disc Diameter (imperial) 0.55 "

Disc Diameter (metric) 14.0 mm

Panel Thickness max. (imperial) 0.08 "

Panel Thickness max. (metric) 2.0 mm

Panel Thickness min. (imperial) 0.02 "

Panel Thickness min. (metric) 0.8 mm

Mounting Hole Diameter D (imperial) 0.26 - 0.28 "

Mounting Hole Diameter D (metric) 6.5 - 7.0 mm

Mounting Hole Diameter D min (imperial)

Mounting Hole Diameter D max 0.28 " (imperial)

Mounting Hole Diameter D max 7.0 mm (metric)

Mounting Hole Diameter D min (metric)

6.5 mm

## Logistics and Packaging

---

<b>Quantity per</b>	bag
<b>Package Quantity</b>	500
<b>Carton Quantity</b>	10000 Pieces
<b>Weight (Metric)</b>	1.3 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes