

155-03800



Article Number: 155-03800

Connector Clip; Hole Dia. 6.5-7.0mm; Panel 0.7-6.0mm/ PA66HIRHS; Black; 500/Pack



Base Data

Local Order Number 155-03800

Type FT6LG m. AMP-Aufnahme

Color Black (BK)

Features and Benefits Connector Clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications. HellermannTyton offers connector clips with robust and detailed designs that include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges. HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.

Fixation Method (FF) Fir Tree

Short Description Connector Clip; Hole Dia. 6.5-7.0mm; Panel 0.7-6.0mm/ PA66HIRHS; Black; 500/Pack

Product Dimensions

Length of Fir Tree 11.1 mm

Disc Diameter (imperial) 0.63 "

Disc Diameter (metric) 16.0 mm

Panel Thickness max. (imperial) 0.24 "

Panel Thickness max. (metric) 6.0 mm

Panel Thickness min. (imperial) 0.03 "

Panel Thickness min. (metric) 0.7 mm

Mounting Hole Diameter D (imperial) 0.26-0.28 "

Mounting Hole Diameter D (metric) 6.5 - 7.0 mm

Mounting Hole Diameter D min (imperial) 0.26 "

Mounting Hole Diameter D max 0.28 "

(imperial)

Mounting Hole Diameter D max 7.0 mm

(metric)
6.5 mm

Mounting Hole Diameter D min (metric)

Logistics and Packaging

Quantity per bag

Package Quantity 500

Carton Quantity 15000 Pieces

Weight (Metric) 0.88 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL94 HB

Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)

ROHS Conformity Yes