

155-05800



Article Number: 155-05800

Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26"-.28", PA66HIRHS, Black, 1,500/pkg

 RoHS

Base Data

Local Order Number	155-05800
Type	T50SOSFT6E
Color	Black (BK)
Features and Benefits	• Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation. • Initial fir tree serves as a locating feature for assistance in blind assembly applications. • Disc feature provides anti-rattle protection in high vibration applications.
Product Description	Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force.
Fixation Method (FF)	Fir Tree
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Outside Serrated
Short Description	Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26"-.28", PA66HIRHS, Black, 1,500/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	50.0 lbs
Minimum Tensile Strength (N)	150 N
Length L (imperial)	6.0 "
Length L (metric)	160 mm
Length of Fir Tree	8.4 mm
Width W (imperial)	0.19 "
Width W (metric)	4.6 mm
Height H (imperial)	0.33 "
Bundle Diameter min (imperial)	0.04 "
Bundle Diameter min (metric)	1.6 mm
Bundle Diameter max (imperial)	1.4 "
Bundle Diameter max (metric)	35.0 mm
Disc Diameter (imperial)	0.63 "
Disc Diameter (metric)	16.0 mm
Panel Thickness max. (imperial)	0.12 "
Panel Thickness max. (metric)	3.0 mm
Panel Thickness min. (imperial)	0.03 "
Panel Thickness min. (metric)	0.75 mm
Mounting Hole Diameter D (imperial)	0.26 - 0.28 "

Mounting Hole Diameter D (metric)	6.5 - 7.0 mm		
Mounting Hole Diameter D min (imperial)	0.26 "	Mounting Hole Diameter D max (imperial)	0.28 "
		Thickness T (imperial)	0.05 "
Mounting Hole Diameter D max (metric)	7.0 mm		
	Mounting Hole Diameter D min (metric)		6.5 mm
Thickness T (Metric)	1.35 mm		

Logistics and Packaging

Quantity per	bag
Package Quantity	1500
Carton Quantity	6000 Pieces
Weight (Metric)	1.31 kg

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Operating Temperature	-40 °F to +221 °F (-40 °C to +105 °C)
ROHS Conformity	Yes